

STRADALE

800

MV Agusta is committed to the constant improvement of our products. Therefore the information and technical characteristics of the vehicles are subject to change without notice.



PEARL WHITE/SAND METALLIC GREY



RED/SILVER



BRONZE METALLIC/PEARL WHITE

ENGINE

Type	Three cylinder, 4 stroke, 12 valve
Timing system	"D.O.H.C" with hydraulic chain tensioner
Total displacement	798 cm ³ (48.7 cu. in.)
Compression ratio	13.3:1
Starting	Electric
Bore x stroke	79.0 mm x 54.3 mm (3.1 in. x 2.1 in.)
Max. power - r.p.m. (at the crankshaft)**	84.5 kW (115 hp) at 11.000 r.p.m.

Max. torque - r.p.m.	78.5 Nm (8.0 kgm) at 9.000 r.p.m.
Cooling system	Cooling with separated liquid and oil radiators

Engine management system	Integrated ignition - injection system MVICS (Motor & Vehicle Integrated Control System) with three injectors. Engine control unit Eldor NEMO EM2.0, throttle body full drive by wire Mikuni Ø 47.0 pencil-coil ELDOR with ion-sensing technology, control of detonation and misfire. Torque control with four maps, Traction Control with eight levels of intervention MV EAS 2.0 (Electronically Assisted Shift)
Electronic quick shift	

Clutch	Hydraulic clutch, wet multi-disc
Transmission	Cassette style; six speed, constant mesh
Primary drive	19/36
Gear ratio	
First gear:	13/37
Second gear:	16/34
Third gear:	18/32
Fourth gear:	19/30
Fifth gear:	21/30
Sixth gear:	22/29
Final drive ratio	16/41

ELECTRICAL EQUIPMENT

Voltage	12 V
Alternator	350 W at 5000 r.p.m.
Battery	12 V - 8.6 Ah

DIMENSIONS AND WEIGHT

Wheelbase	1460 mm (57.48 in.)
Overall length	2130 mm (83.86 in.)
Overall width	890 mm (35.04 in.)
Saddle height	870 mm (34.25 in.)
Min. ground clearance	125 mm (4.92 in.)
Trail	109 mm (4.29 in.)
Dry weight	181 kg (399 lbs.)
Fuel tank capacity	16 l (4.23 U.S. gal.)

PERFORMANCE

Maximum speed*	214.0 km/h (133 mph)
----------------	----------------------

FRAME

Type	ALS Steel tubular trellis
Rear swing arm pivot plates material	Aluminium alloy

FRONT SUSPENSION

Type	Marzocchi "UPSIDE DOWN" telescopic hydraulic fork with rebound-compression damping and spring preload external and separate adjustment
Fork dia.	43 mm (1.69 in.)
Fork travel	150 mm (5.91 in.)

REAR SUSPENSION

Type	Progressive Sachs, single shock absorber with rebound and compression damping and spring preload adjustment
Single sided swing arm material	Aluminium alloy
Wheel travel	150 mm (5.91 in.)

BRAKES

Front brake	Double floating disc with Ø 320 mm (Ø 12.6 in.) diameter, with steel braking disc and flange
Front brake caliper	Brembo radial-type, with 4 pistons Ø 32 mm (Ø 1.26 in.)
Rear brake	Single steel disc with Ø 220 mm (Ø 8.66 in.) dia.
Rear brake caliper	Brembo with 2 pistons - Ø 34 mm (Ø 1.34 in.)
ABS System	Bosch 9 Plus with RLM (Rear wheel Lift-up Mitigation)

WHEELS

Front: Material/size	Aluminium alloy 3.50 " x 17 "
Rear: Material/size	Aluminium alloy 5.50 " x 17 "

TYRES

Front	120/70 - ZR 17 M/C (58 W)
Rear	180/55 - ZR 17 M/C (73 W)

FAIRING

Material	Thermoplastic
----------	---------------

* Top speed attained on closed course.

** Limited power versions available on demand.

Every country could have a price variation due to local import duties and taxes.